

The ecomet Advantage

- Fuel efficient 'H' Series engine with Inline FIP
- 120 HP Power with 415 Nm torque
- Higher gradeability
- Wide & spacious cabin
- Heavy duty aggregates

Applications

- Blue Metal
- Construction
- Sand / Earthwork
- Projects

Anytime, Anywhere Service

Nationwide coverage through strong network of:

- Ashok Leyland trained mechanics
- Readily available spare parts LEYPARTS
- Leyland Direct 24 x 7 National Helpline Service
- Mobile service vans & service bikes



Original Quality Parts



24 x 7 National Helpline



Express Service Bikes
Express Service Vans



Best-in-class warranty

24 x 7

The specifications are liable to change due to continuous improvements and are for reference only. Do not drill or weld on frame

Specifications			
Engine	H'series 4 cylinder with inline FIP, BS III		
Maximum power	120 HP @2400 rpm		
Maximum torque	415 Nm @1400 rpm		
Clutch	330 mm Dia single plate dry type-Hydraulic actuation		
Gear box	Synchromesh 6S ODGB		
FGR	8.28		
Gradeability	41%		
Steering	Power steering		
Frame	All steel ladder type with bolted construction		
Front axle	I section reverse elliot		
Rear axle	Fully floating Hypoid with 6.14:1 RAR		
Suspension	Shackle ended - Multileaf springs		
Cabin	All steel factory built tiltable day cabin		
Brakes	Full air-dual line S-cam brakes		
Parking brakes	Spring actuated, Pneumatic (on Rear only)		
Battery	12 V-100 AH		
Tyres	8.25X16 16PR		
Fuel tank	115lts		
GVW	10.900 Kgs		

Major Dimensions (in mm)			
Wheelbase	2850	Load Body (Internal)	3407X2100X710 mm
Front Overhang	1338	Floor Plate Thickness	8 mm
Rear Overhang	1144	Side Board Thickness	3 mm
Overall Length	5332	Tail Door Thickness	3 mm
Overall Width	2200	Tipping Angle	47 degrees
Front Track	1946	Tipping Time	15sec@2400 rpm
Rear Track	1675	Return Time	11 sec
Turning Circle dia	10700	Oil Tank capacity	32 lts

Authorized Dealer